



TECHNICAL DESCRIPTION S800-Vor2_TB_US - 13.10.2017 - www.vs-furniture.com

Series 800 Preliminary remark - body construction.

Series 800 element cabinets are supplied fully glued or disassembled, with eccentric connectors. The row of holes (dia. 1/8") at a grid distance of 1" can be used right through.

Shelf carriers (load class L75) are screwed into standard-equipped cabinets [1] and screwed and inserted into individually equipped cabinets [2].

Adjustable shelf inserts [3] made from LIGNOpal (up to a width of 31 1/2"), coreboard (width 15 3/4"- 47 1/4") and sheet steel (width 15 3/4"- 47 1/4") have a concealed mounting for the shelf carriers.

Vertical body structures are fashioned by glued and, in the case of disassembled cabinets, by construction shelves [4] with eccentric connectors.

Horizontal body structures are fashioned by middle partitions flush with the body [5] or set back [6]. These are glued or, in the case of disassembled cabinets, equipped with eccentric connectors. Middle partitions flush with the body permit the use of separately closing single swing doors. Set-back partitions are combined with double swing doors. Bases are a structural component of the body construction made from LIGNOpal [7] or are positioned as a steel base [8] at heights of 3" and 1 5/8" below the body. Both base types have precision height adjustment by means of an Allen key [9] through the bottom shelf. The LIGNOpal base can be fitted with a base cover strip flush with the front/door [10]. Base recesses [11] on the back are possible in the case of floor strips.

Wardrobe and washbasin cabinets are provided with plastic ventilation outlets on the top and bottom edges of the door.

Construction: Models from a height of 77 5/8" or models with drawers and/or pullouts (DGUV Regel 108-007) must be secured to the wall or floor.

Series 800	Cupboard w	15 3/4	19 3/4	23 5/8	31 1/2	35 1/2	39 3/8	47 1/4	31 1/2	35 1/2	39 3/8	47 1/4	47 1/4	47 1/4
Profil 800	Shelf w	14 1/4	18 1/8	22 1/8	30	33 7/8	37 7/8	45 3/4	14 5/8	16 5/8	18 5/8	22 1/2	14 3/4	10 7/8
	Middle partition				--					1			2	3
	Load according to	22	28	33	46	52	59	70	22	24	28	30	22	15
	*D=16 3/4													
	*D=22 7/8	30	39	48	66	74	83	101	24	35	39	48	30	