



**PRODUCT INFORMATION** S2000-M\_TY\_US - 23.06.2023 - [www.vsamerica.com](http://www.vsamerica.com)

## Series 2000 Typ M. Functional partition.

System of mobile individual elements.

Frame construction with an all-round aluminum profile section and a filler element. Side profile section with a vertical functional rebate and an integrated pull-out plastic welt for tool-free joining of two functional screens. Filler element 1. Melamine-resin-coated chipboard. 2. Magnetically adherent enamel-coated chipboard. 3. From a lightweight top with fabric covering. 4. Melamine-resin-coated acoustic panel with slotting. 5. Double-section panel.

Support element consisting of short and long stabilisers with castors.

Note. The maximum load must not be exceeded when integrating accessories in the function groove (see table). The following material groups are available: Frame made of aluminum: M(anodisé); Stabiliser and foot made of aluminum: M(arctic, black RAL 9011); Writing surface made of steel: E(white); Fabric cover: S46,52,74,78,79,80; Acoustic front made of chipboard: L10; Front made of chipboard: L6.

|                      |                            |  |                  |                  |                  |                  |
|----------------------|----------------------------|--|------------------|------------------|------------------|------------------|
|                      |                            |  |                  |                  |                  |                  |
| Series 2000<br>Typ M | Total h = 48 $\frac{3}{8}$ |  | 05400            | 05401            | 05402            | 05403            |
|                      | Total h = 63 $\frac{3}{8}$ |  | 05405            | 05406            | 05407            | 05408            |
|                      | Total h = 78 $\frac{3}{8}$ |  | 05410            | 05411            | 05412            | 05413            |
|                      | w                          |  | 31 $\frac{1}{2}$ | 35 $\frac{1}{2}$ | 39 $\frac{3}{8}$ | 47 $\frac{1}{2}$ |
|                      | maximum load lb            |  | 66,1             |                  |                  |                  |